

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
20 October 2005 (20.10.2005)

PCT

(10) International Publication Number
WO 2005/098222 A1

(51) International Patent Classification⁷: **F02D 41/02**,
41/40, 41/00

[JP/JP]; Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho,
Toyota-shi, Aichi-ken 471-8571 (JP).

(21) International Application Number:
PCT/IB2005/000838

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(22) International Filing Date: 31 March 2005 (31.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-111251 5 April 2004 (05.04.2004) JP

(71) Applicant (for all designated States except US): **TOY-
OTA JIDOSHA KABUSHIKI KAISHA** [JP/JP]; 1, Toy-
ota-cho, Toyota-shi, Aichi-ken 471-8561 (JP).


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

(72) Inventor; and

(75) Inventor/Applicant (for US only): **KOGO, Tomoyuki**

[Continued on next page]

(54) Title: EXHAUST GAS CONTROL APPARATUS AND EXHAUST GAS CONTROL METHOD FOR INTERNAL COM-
BUSTION ENGINE



(57) Abstract: In an exhaust gas control apparatus for an internal combustion engine, including a supercharger which is provided in an exhaust passage at a position upstream of a catalyst having an oxidizing ability; turbine rotation energy amount adjusting means (106) for adjusting an amount of energy of exhaust gas, which is used for rotating the turbine of the supercharger; and after-injection performing means for performing after-injection, when a work amount of the compressor is increased by the after-injection, the turbine rotation energy amount adjusting means decreases the amount of energy of the exhaust gas, which is used for rotating the turbine, in order to decrease the increased work amount to zero.

WO 2005/098222 A1



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*